

Package ‘Largevars’

January 20, 2025

Type Package

Title Testing Large VARs for the Presence of Cointegration

Version 1.0.2

Maintainer Eszter Kiss <ekiss2803@gmail.com>

Description Conducts a cointegration test for high-dimensional vector autoregressions (VARs) of order k based on the large N, T asymptotics of Bykhovskaya and Gorin, 2022 (<[doi:10.48550/arXiv.2202.07150](https://doi.org/10.48550/arXiv.2202.07150)>). The implemented test is a modification of the Johansen likelihood ratio test. In the absence of cointegration the test converges to the partial sum of the Airy-1 point process. This package contains simulated quantiles of the first ten partial sums of the Airy-1 point process that are precise up to the first three digits.

Encoding UTF-8

LazyData true

RoxygenNote 7.3.2

Depends R (>= 3.5.0)

Imports methods, graphics, stats, utils

Suggests testthat (>= 3.0.0), tibble (>= 3.0.0), data.table (>= 1.14.0), readr (>= 2.1.0)

Config/testthat/edition 3

License MIT + file LICENSE

URL <https://github.com/eszter-kiss/Largevars>

NeedsCompilation no

Author Anna Bykhovskaya [aut],
Vadim Gorin [aut],
Eszter Kiss [cre, aut]

Repository CRAN

Date/Publication 2024-10-31 13:40:41 UTC

Contents

largevar	2
percentiles	3
quantile_tables	3
sim_function	4
s_p100_price_adj	5
Index	6

largevar	<i>Cointegration test for settings of large N and T</i>
----------	---

Description

Runs the Bykhovskaya-Gorin test for cointegration. Paper can be found at: <https://doi.org/10.48550/arXiv.2202.07150>

Usage

```
largevar(
  data = NULL,
  k = 1,
  r = 1,
  fin_sample_corr = FALSE,
  plot_output = TRUE,
  significance_level = 0.05
)
```

Arguments

data	A numeric matrix where the columns contain individual time series that will be examined for the presence of cointegrating relationships.
k	The number of lags that we wish to employ in the vector autoregression. The default value is $k = 1$.
r	The number of largest eigenvalues used in the test. The default value is $r = 1$.
fin_sample_corr	A boolean variable indicating whether we wish to employ finite sample correction on our test statistic. The default value is <code>fin_sample_corr = FALSE</code> .
plot_output	A boolean variable indicating whether we wish to generate a plot of the empirical distribution of eigenvalues. The default value <code>plot_output = TRUE</code> .
significance_level	Specify the significance level at which the decision about H_0 should be made. The default value is <code>significance_level = 0.05</code> .

Value

A list that contains the test statistic, a table with theoretical quantiles presented for $r=1$ to $r=10$, and the decision about H_0 at the significance level specified by the user.

Examples

```

largevar(
  data = matrix(rnorm(60, mean = 0.05, sd = 0.01), 20, 3),
  k = 1,
  r = 1,
  fin_sample_corr = FALSE,
  plot_output = FALSE,
  significance_level = 0.05
)

```

percentiles	<i>Quantiles for the limiting distribution of the test</i>
-------------	--

Description

A data frame containing the simulated quantiles for the test statistic used in the `largevar` function. More details about how these simulations were conducted can be found in Section 4 of the vignette.

Format

A data frame with 99 rows and 11 variables:

Source

Calculated through own simulations (see details in Section 4 of vignette).

quantile_tables	<i>Creates the quantile table output for largevar function</i>
-----------------	--

Description

Outputs the quantile tables from the package's corresponding vignette.

Usage

```
quantile_tables(r = 1)
```

Arguments

<code>r</code>	Which partial sum the quantile table should be returned for. (Only $r \leq 10$ is available.) Default is $r=1$.
----------------	--

Value

A numeric matrix.

Examples

```
quantile_tables(r=3)
```

 sim_function

Empirical p-value for cointegration test

Description

Runs a simulation on the H0 for the Bykhovskaya-Gorin test for cointegration and returns an empirical p-value. Paper can be found at: <https://doi.org/10.48550/arXiv.2202.07150>

Usage

```
sim_function(
  N = NULL,
  tau = NULL,
  stat_value = NULL,
  k = 1,
  r = 1,
  fin_sample_corr = FALSE,
  sim_num = 1000
)
```

Arguments

N	The number of time series used in simulations.
tau	The length of the time series used in simulations.
stat_value	The test statistic value for which the p-value is calculated.
k	The number of lags that we wish to employ in the vector autoregression. The default value is k = 1.
r	The number of largest eigenvalues used in the test. The default value is r = 1.
fin_sample_corr	A boolean variable indicating whether we wish to employ finite sample correction on our test statistics. The default value is fin_sample_corr = FALSE.
sim_num	The number of simulations that the function conducts for H0. The default value is sim_num = 1000.

Value

A list that contains the simulation values, the empirical percentage (realizations larger than the test statistic provided by the user) and a histogram.

Examples

```
sim_function(N=90, tau=501, stat_value=-0.27,k=1,r=1,sim_num=30)
```

s_p100_price_adj	<i>Stock price data for example in vignette</i>
------------------	---

Description

A data frame containing weekly S&P100 prices over ten years: 01.01.2010 - 01.01.2020, The S&P100 includes 101 leading U.S. stocks of which 92 were collected here.

Format

A data frame with 522 rows and 93 variables:

Source

Refer to the data source used in: A. Bykhovskaya and V. Gorin. Cointegration in large vars. *Annals of Statistics*, 2022.

Index

largevar, [2](#)

percentiles, [3](#)

quantile_tables, [3](#)

s_p100_price_adj, [5](#)

sim_function, [4](#)