

# Package ‘dataclass’

August 7, 2023

**Type** Package

**Title** Easily Create Structured Lists or Data Frames with Input Validation

**Version** 0.3.0

**Description** Easily define templates for lists and data frames that validate each element. Specify the expected type (i.e., character, numeric, etc), expected length, minimum and maximum values, allowable values, and more for each element in your data. Decide whether violations of these expectations should throw an error or a warning. This package is useful for validating data within R processes which pull from dynamic data sources such as databases and web APIs to provide an extra layer of validation around input and output data.

**License** MIT + file LICENSE

**Encoding** UTF-8

**Imports** purrr, rlang, glue, magrittr, tibble, cli, dplyr

**RoxygenNote** 7.2.3

**NeedsCompilation** no

**Suggests** testthat (>= 3.0.0)

**Config/testthat/edition** 3

**Author** Chris Walker [aut, cre, cph]

**Maintainer** Chris Walker <walkerjameschris@gmail.com>

**Repository** CRAN

**Date/Publication** 2023-08-07 17:10:08 UTC

## R topics documented:

any_obj	2
atm_vec	3
chr_vec	4
dataclass	5
data_validator	7

df_like . . . . .	8
dte_vec . . . . .	9
lgl_vec . . . . .	10
num_vec . . . . .	11

<b>Index</b>	<b>13</b>
--------------	-----------

---

any_obj	<i>Validator: Allow any object</i>
---------	------------------------------------

---

### Description

This function is used to bypass dataclass checks for a given element. If you do not want dataclass to check a given element, set the element equal to `any_obj()` to allow any object. Keep in mind that while dataclass will bypass the check, the object must still be a valid R object. Furthermore, if you are using dataclass to create a tibble, then the object must be a valid tibble column type, even if additional checks are not considered. This can be dangerous because dataclass is designed to check objects, not bypass them. Use this validator sparingly and consider how you can write a stricter dataclass.

### Usage

```
any_obj()
```

### Value

A function with the following properties:

\* Always returns TRUE \* Bypasses any dataclass checks

### Examples

```
# Define a dataclass:
my_dataclass <-
  dataclass(
    date_val = dte_vec(),
    anything = any_obj()
  )

# While `date_val` must be a date, `anything` can be any value!
my_dataclass(
  date_val = as.Date("2022-01-01"),
  anything = lm(vs ~ am, mtcars)
)

my_dataclass(
  date_val = as.Date("2022-01-01"),
  anything = c(1, 2, 3, 4, 5)
)

my_dataclass(
```

```

    date_val = as.Date("2022-01-01"),
    anything = list(a = 1, b = 2)
  )

```

---

atm\_vec

*Validator: Check if element is atomic*


---

## Description

This function is used to check whether something is atomic. Atomic elements are represented by simple vectors, (i.e., numeric, logical, character) but also include special vectors like date vectors. You can use this function to check the length of a vector. You can also specify the level of a violation. If level is set to "warn" then invalid inputs will warn you. However, if level is set to "error" then invalid inputs will abort.

## Usage

```

atm_vec(
  max_len = Inf,
  min_len = 1,
  level = "error",
  allow_na = FALSE,
  allow_dups = TRUE
)

```

## Arguments

max_len	The maximum length of an atomic element
min_len	The minimum length of an atomic element
level	Setting "warn" throws a warning, setting "error" halts
allow_na	Should NA values be allowed?
allow_dups	Should duplicates be allowed?

## Value

A function with the following properties:

- \* Checks whether something is atomic
- \* Determines whether the check will throw warning or error
- \* Optionally checks for element length

## Examples

```

# Define a dataclass for testing atomic:
my_dataclass <-
  dataclass(
    num_val = num_vec(),
    # Setting warn means a warning will occur if violation is found
    # The default is "error" which is stricter and will halt upon violation
  )

```

```

    atm_val = atm_vec(level = "warn")
  )

# While `num_val` must be a number, `atm_val` can be any atomic element!
my_dataclass(
  num_val = c(1, 2, 3),
  atm_val = Sys.Date()
)

my_dataclass(
  num_val = c(1, 2, 3),
  atm_val = c(TRUE, FALSE)
)

my_dataclass(
  num_val = c(1, 2, 3),
  atm_val = c("This is", "a character!")
)

```

---

chr\_vec

*Validator: Check if element is a character*


---

### Description

This function is used to check whether something is a character. You can use this function to check the length and allowable values of character. You can also specify the level of a violation. If level is set to "warn" then invalid inputs will warn you. However, if level is set to "error" then invalid inputs will abort.

### Usage

```

chr_vec(
  max_len = Inf,
  min_len = 1,
  allowed = NA,
  level = "error",
  allow_na = FALSE,
  allow_dups = TRUE
)

```

### Arguments

max_len	The maximum length of a character element
min_len	The minimum length of a character element
allowed	A vector of allowable values
level	Setting "warn" throws a warning, setting "error" halts
allow_na	Should NA values be allowed?
allow_dups	Should duplicates be allowed?

**Value**

A function with the following properties:

\* Checks whether something is a character vector \* Determines whether the check will throw warning or error \* Optionally checks for element length \* Optionally checks for allowable values

**Examples**

```
# Define a dataclass for testing characters:
my_dataclass <-
  dataclass(
    string = chr_vec(allowed = c("this", "or", "that")),
    other_string = chr_vec()
  )

# `string` must be one of these: `c("this", "or", "that")`
my_dataclass(
  string = "this",
  other_string = "I can be anything I want (as long as I am a string)"
)
```

---

dataclass

*Construct a dataclass in R*

---

**Description**

Building a dataclass is easy! Provide names for each of the elements you want in your dataclass and an associated validator. The dataclass package comes with several built in validators, but you can define a custom validator as an anonymous function or named function to be bundled with your dataclass.

**Usage**

```
dataclass(...)
```

**Arguments**

... Elements to validate (i.e., `dte_vec()` will validate a date vector)

**Details**

`dataclass()` will return a new function with named arguments for each of the elements you define here. If you want to use your dataclass on data frames or tibbles you must pass the dataclass to `data_validator()` to modify behavior.

**Value**

A function with the following properties:

\* An argument for each element provided to dataclass() \* Each argument in the returned function will validate inputs \* An error occurs if new elements passed to the returned function are invalid \* List is returned if new elements passed to the returned function are valid

**Examples**

```
my_dataclass <- dataclass(
  min_date = dte_vec(1), # Ensures min_date is a date vector of length 1
  max_date = dte_vec(1), # Ensures max_date is a date vector of length 1
  run_data = df_like(), # Ensures run_data is a data object (i.e. tibble)
  run_note = chr_vec(1) # Ensures run_note is a character vector of length 1
)

# This returns a validated list!
my_dataclass(
  min_date = as.Date("2022-01-01"),
  max_date = as.Date("2023-01-01"),
  run_data = head(mtcars, 2),
  run_note = "A note!"
)

# An example with anonymous functions
a_new_dataclass <-
  dataclass(
    start_date = dte_vec(1),
    # Ensures calculation is a column in this data and is data like
    results_df = function(df) "calculation" %in% colnames(df)
  )

# Define a dataclass for creating data! Wrap in data_validator():
my_df_dataclass <-
  dataclass(
    dte_col = dte_vec(),
    chr_col = chr_vec(),
    # Custom column validator ensures values are positive!
    new_col = function(x) all(x > 0)
  ) |>
  data_validator()

# Validate a data frame or data frame like objects!
data.frame(
  dte_col = as.Date("2022-01-01"),
  chr_col = "String!",
  new_col = 100
) |>
my_df_dataclass()
```

---

data_validator	<i>Convert a dataclass to a data frame validator</i>
----------------	--

---

### Description

If you intend to use your dataclass to validate data frame like object such as tibbles, data frames, or data tables, pass the dataclass into this function to modify behavior.

### Usage

```
data_validator(x, strict_cols = TRUE)
```

### Arguments

x	A dataclass object
strict_cols	Should additional columns be allowed in the output?

### Value

A function with the following properties:

- \* A modified dataclass function designed to accept data frames
- \* A single argument to test new data frames
- \* Each column in a new data frame will be tested
- \* An error occurs if new data passed to the returned function are invalid
- \* Data is returned if new data passed to the returned function are valid

### Examples

```
# Define a dataclass for creating data! Pass to data_validator():
my_df_dataclass <-
  dataclass(
    dte_col = dte_vec(),
    chr_col = chr_vec(),
    # Custom column validator ensures values are positive!
    new_col = function(x) all(x > 0)
  ) |>
  data_validator()

# Validate a data frame or data frame like objects!
data.frame(
  dte_col = as.Date("2022-01-01"),
  chr_col = "String!",
  new_col = 100
) |>
  my_df_dataclass()

# Allow additional columns in output
test_df_class <-
  dataclass(
    dte_col = dte_vec()
  ) |>
```

```

data_validator(strict_cols = FALSE)

tibble::tibble(
  dte_col = as.Date("2022-01-01"),
  other_col = "a"
) |>
  test_df_class()

```

---

df\_like

*Validator: Check if element is a data like object*


---

### Description

This function is used to check whether something is data like. You can use this function to check the data row count. You can also specify the level of a violation. If level is set to "warn" then invalid inputs will warn you. However, if level is set to "error" then invalid inputs will abort.

### Usage

```
df_like(max_row = Inf, min_row = 1, level = "error")
```

### Arguments

max_row	The maximum row count of a data element
min_row	The minimum row count of a data element
level	Setting "warn" throws a warning, setting "error" halts

### Value

A function with the following properties:

- \* Checks whether something is a data frame like object
- \* Determines whether the check will throw warning or error
- \* Optionally checks for row count

### Examples

```

# Define a dataclass for testing data:
my_dataclass <-
  dataclass(
    df = df_like(100)
  )

# `df` must be a data like object with at most 100 rows!
my_dataclass(
  df = mtcars
)

```



---

`dte_vec`*Validator: Check if element is a date*

---

## Description

This function is used to check whether something is a date. You can use this function to check the length of a date vector. You can also specify the level of a violation. If level is set to "warn" then invalid inputs will warn you. However, if level is set to "error" then invalid inputs will abort.

## Usage

```
dte_vec(  
  max_len = Inf,  
  min_len = 1,  
  level = "error",  
  allow_na = FALSE,  
  allow_dups = TRUE  
)
```

## Arguments

<code>max_len</code>	The maximum length of a date element
<code>min_len</code>	The minimum length of a date element
<code>level</code>	Setting "warn" throws a warning, setting "error" halts
<code>allow_na</code>	Should NA values be allowed?
<code>allow_dups</code>	Should duplicates be allowed?

## Value

A function with the following properties:

- \* Checks whether something is a date
- \* Determines whether the check will throw warning or error
- \* Optionally checks for element length

## Examples

```
# Define a dataclass for testing dates:  
my_dataclass <-  
  dataclass(  
    num_val = num_vec(),  
    # Setting warn means a warning will occur if violation is found  
    # The default is "error" which is stricter and will halt upon violation  
    dte_val = dte_vec(level = "warn")  
  )  
  
# While `num_val` must be a number, `dte_val` must be a date!  
my_dataclass(  
  num_val = c(1, 2, 3),
```

```

    dte_val = Sys.Date()
  )

  my_dataclass(
    num_val = c(1, 2, 3),
    dte_val = as.Date("2022-01-01")
  )

  my_dataclass(
    num_val = c(1, 2, 3),
    dte_val = as.Date(c("2022-01-01", "2023-01-01"))
  )

```

---

lgl\_vec

---

*Validator: Check if element is a logical*


---

### Description

This function is used to check whether something is a logical. You can use this function to check the length of a logical vector. You can also specify the level of a violation. If level is set to "warn" then invalid inputs will warn you. However, if level is set to "error" then invalid inputs will abort.

### Usage

```
lgl_vec(max_len = Inf, min_len = 1, level = "error", allow_na = FALSE)
```

### Arguments

max_len	The maximum length of a logical element
min_len	The minimum length of a logical element
level	Setting "warn" throws a warning, setting "error" halts
allow_na	Should NA values be allowed?

### Value

A function with the following properties:

- \* Checks whether something is a logical vector
- \* Determines whether the check will throw warning or error
- \* Optionally checks for element length

### Examples

```

# Define a dataclass for testing logicals:
my_dataclass <-
  dataclass(
    bool = lgl_vec()
  )

# `bool` must be a logical vector of any length!

```

```
my_dataclass(
  bool = TRUE
)
```

---

num\_vec

*Validator: Check if element is a number*


---

## Description

This function is used to check whether something is a number. You can use this function to check the length and min-max of a number vector. You can also specify the level of a violation. If level is set to "warn" then invalid inputs will warn you. However, if level is set to "error" then invalid inputs will abort.

## Usage

```
num_vec(
  max_len = Inf,
  min_len = 1,
  max_val = Inf,
  min_val = -Inf,
  allowed = NA,
  level = "error",
  allow_na = FALSE,
  allow_dups = TRUE
)
```

## Arguments

max_len	The maximum length of a numeric element
min_len	The minimum length of a numeric element
max_val	The maximum value of a numeric element
min_val	The minimum value of a numeric element
allowed	A vector of allowable values
level	Setting "warn" throws a warning, setting "error" halts
allow_na	Should NA values be allowed?
allow_dups	Should duplicates be allowed?

## Value

A function with the following properties:

- \* Checks whether something is a number vector
- \* Determines whether the check will throw warning or error
- \* Optionally checks for element length
- \* Optionally checks for allowable values
- \* Optionally checks for max/min

## Examples

```
# Define a dataclass for testing numbers:
my_dataclass <-
  dataclass(
    dte_val = dte_vec(),
    # Setting warn means a warning will occur if violation is found
    # The default is "error" which is stricter and will halt upon violation
    # We also set allowed to 0 and 1 which means elements must be 0 or 1
    num_val = num_vec(level = "warn", allowed = c(0, 1))
  )

# While `dte_val` must be a date, `num_val` must be 0 or 1!
my_dataclass(
  dte_val = Sys.Date(),
  num_val = c(0, 1, 1, 0, 1)
)

my_dataclass(
  dte_val = Sys.Date(),
  num_val = 1
)

# Set min and max requirements!
test_dataclass <-
  dataclass(
    num = num_vec(min_val = 1, max_val = 100)
  )

# Value must be between 1 and 10 inclusive!
test_dataclass(num = 10.03012)
```

# Index

any\_obj, [2](#)  
atm\_vec, [3](#)

chr\_vec, [4](#)

data\_validator, [7](#)  
dataclass, [5](#)  
df\_like, [8](#)  
dte\_vec, [9](#)

lgl\_vec, [10](#)

num\_vec, [11](#)