

Package ‘micvar’

December 8, 2025

Type Package

Title Order Selection in Vector Autoregression by Mean Square Information Criteria

Version 0.1.0

Description Implements order selection for Vector Autoregressive (VAR) models using the Mean Square Information Criterion (MIC). Unlike standard methods such as AIC and BIC, MIC is likelihood-free. This method consistently estimates VAR order and has robust performance under model misspecification. For more details, see Hellstern and Shojaie (2025) <[doi:10.48550/arXiv.2511.19761](https://doi.org/10.48550/arXiv.2511.19761)>.

License GPL (>= 3)

Encoding UTF-8

RoxygenNote 7.3.1

Imports MASS, matrixcalc, Rdpack, stats

RdMacros Rdpack

NeedsCompilation no

Author Michael Hellstern [aut, cre]

Maintainer Michael Hellstern <mikeh1@uw.edu>

Repository CRAN

Date/Publication 2025-12-08 08:10:10 UTC

Contents

| | |
|----------------------------|---|
| gen_coef_mat | 2 |
| micvar | 2 |
| sim_var | 4 |
| verify_stability | 5 |

| | |
|--------------|----------|
| Index | 7 |
|--------------|----------|

gen_coef_mat

Simulate coefficient matrices with specified density

Description

Simulates coefficient matrices used to generate data from a vector autoregressive process.

Usage

```
gen_coef_mat(k, coefmin, coefmax, dens)
```

Arguments

| | |
|---------|---|
| k | Integer. Dimension of process. |
| coefmin | Numeric. Minimum value of coefficient. See Details. |
| coefmax | Numeric. Maximum value of coefficient. See Details. |
| dens | Numeric. Must be between 0 and 1. Specifies the proportion of non-zero entries in the coefficient matrix. The number of non-zero entries is computed as $\text{floor}(k^2 \cdot \text{dens})$. |

Details

Coefficient values are drawn from a $\text{Uniform}(\text{coefmin}, \text{coefmax})$ or a $\text{Uniform}(-\text{coefmax}, -\text{coefmin})$ each with 50% probability.

Value

k x k matrix.

Examples

```
# bivariate coefficient matrix
coefmat <- gen_coef_mat(k = 2, coefmin = 0.1, coefmax = 0.3, dens = 0.8)
print(coefmat)
```

micvar*Estimate order by mean square information criteria (MIC)*

Description

Fits an autoregressive model to the data where the order is selected by minimizing the mean square information criteria. Model fitting is performed using [ar](#). Any of the methods available in the method argument of [ar](#) can be used.

Usage

```
micvar(
  x,
  pmax,
  pmaxst = 2 * pmax,
  method = "ols",
  na.action = stats::na.fail,
  series = deparse1(substitute(x)),
  demean = TRUE,
  ...
)
```

Arguments

| | |
|-----------|--|
| x | n x p time series data matrix. Can be univariate or multivariate time series. If x is not a matrix it will be coerced using <code>as.matrix(x)</code> . |
| pmax | Integer. Maximum number of lags to consider. Considered lags will be $0, 1, \dots, pmax$. |
| pmaxst | Integer (default is <code>2pmax</code>). Maximum lag used for computing self-tuned lambda. Must be larger than pmax. |
| method | Character string (default is "ols"). Specifies method to fit the model. Options are: <code>c("ols", "burg", "mle", "yule-walker", "yw")</code> . Note this function uses <code>ar</code> to perform model fitting. |
| na.action | Function for missing values (default is <code>na.fail</code>). See the <code>na.action</code> argument in <code>ar</code> . |
| series | Character string. Name of series. See the <code>series</code> argument in <code>ar</code> . |
| demean | Boolean (default is <code>TRUE</code>). Whether or not to demean the series. See the <code>demean</code> argument in <code>ar</code> . |
| ... | Additional arguments for specific method. See <code>ar</code> and its various methods such as <code>ar.yw</code> and <code>ar.ols</code> and their corresponding arguments. |

Details

This function uses the `ar` functions for fitting. For relevant details of those methods see the Details section of `ar`.

Value

List with elements. Many of these elements are similar to `ar`.

| | |
|------------------|--|
| order | Order of fitted model selected by MIC |
| penalized_losses | Numeric vector of penalized losses for orders $0, 1, \dots, pmax$. |
| ar | Estimated autoregression coefficients. See the <code>ar</code> return value from <code>ar</code> . |
| var.pred | Prediction variance. See the <code>var.pred</code> return value from <code>ar</code> . |
| x.mean | Estimated mean. See the <code>x.mean</code> return value from <code>ar</code> . |

| | |
|--------------|---|
| x.intercept | Intercept. See the x.intercept return value from ar . |
| n.used | Number of observations in the time series including missing. See the n.used return value from ar . |
| n.obs | Number of non-missing observations. See the n.obs return value from ar . |
| pmax | The value of pmax argument. |
| partialacf | Estimate of partial autocorrelation. See the partialacf return value from ar . |
| resid | Residuals from fitted model. See the resid return value from ar . |
| method | Value of method argument. |
| series | Name of the series. See the series return value from ar . |
| call | Function call. |
| asy.var.coef | Asymptotic-theory variance matrix of coefficient estimates. See the asy.var.coef return value from ar . |

Examples

```
# multivariate example - default is OLS
VAR3_2_A <- list(gen_coef_mat(3, 0.1, 0.3, 0.8), # lag 1
                gen_coef_mat(3, 0.1, 0.4, 0.5)) # lag 2
x <- sim_var(VAR3_2_A, n = 5000)
mic_model <- micvar(x, pmax = 10)

# burg and yule-walker examples
mic_model_burg <- micvar(x, pmax = 10, method = "burg")
mic_model_yw <- micvar(x, pmax = 10, method = "yw")

# univariate example
ar_coefs <- list(matrix(0.3,nrow=1), matrix(0.1,nrow=1))
x <- sim_var(ar_coefs, n = 5000)
mic_model <- micvar(x, pmax = 10)
```

| | |
|---------|---|
| sim_var | <i>Simulate data from a vector autoregressive model with specified coefficient matrices</i> |
|---------|---|

Description

Simulates data from a stable vector autoregressive model with Gaussian innovations and specified coefficient matrices. Stability of the process is verified using [verify_stability](#).

Usage

```
sim_var(A, n, mu = NULL, Sigma = NULL, burn_in = 500)
```

Arguments

| | |
|---------|---|
| A | List of coefficient matrices. Each element in A must be a square matrix. Dimension of matrix determines the number of variables. Length of A determines the order of the process. In the case of univariate time series each entry of A should be a 1 x 1 matrix. |
| n | Integer. Number of data points to simulate. |
| mu | Vector (default 0s). Means of Gaussian innovations. |
| Sigma | Square matrix (default Identity). Variance of Gaussian innovations. |
| burn_in | Integer (default 500). Number of observations used to start up simulated process. In total n + burn_in observations are simulated but the first burn_in are discarded. |

Value

n x k data matrix.

Examples

```
# multivariate
VAR3_2_A <- list(gen_coef_mat(3, 0.1, 0.3, 0.8), # lag 1
                gen_coef_mat(3, 0.1, 0.4, 0.5)) # lag 2
x <- sim_var(VAR3_2_A, n = 1000)

# univariate
AR2 <- list(matrix(0.5), matrix(0.2))
x <- sim_var(AR2, n = 1000)

# non-identity covariance of Gaussian innovations
Sigma <- matrix(c(1,0.5,0.9,0.5,1.5,0.7,0.9,0.7,1.25), nrow = 3)
x <- sim_var(VAR3_2_A, n = 1000, Sigma = Sigma)
```

verify_stability

Verify stability of a vector autoregressive model

Description

Stability is verified using the method the method on pages 14-17 of (Lütkepohl 2005). Specifically we generate the coefficient matrix for the VAR(1) representation of the process and check that all eigenvalues have modulus less than 1.

Usage

```
verify_stability(A)
```

Arguments

| | |
|---|-------------------------------|
| A | List of coefficient matrices. |
|---|-------------------------------|

Value

None. Throws error if not stable process.

References

Lütkepohl H (2005). *New introduction to multiple time series analysis*. Springer Science & Business Media.

Examples

```
VAR3_2_A <- list(gen_coef_mat(3, 0.1, 0.3, 0.8), # lag 1  
               gen_coef_mat(3, 0.1, 0.4, 0.5)) # lag 2  
verify_stability(VAR3_2_A)
```

Index

ar, [2–4](#)

ar.ols, [3](#)

ar.yw, [3](#)

gen_coef_mat, [2](#)

micvar, [2](#)

sim_var, [4](#)

verify_stability, [4, 5](#)